


MOCCA M PRO

“Mocca - The all-in-one cylindrical solution. Mocca is our interpretation of an all integrated cylindrical spotlight. The cooling is passive, being all silent, by allowing cold air to flow from the middle of the cylinder and out in the back. By choosing Mocca you will get a uncluttered environment focusing on the essential: The simplicity of the spotlight and the effect of the light. Developed and produced in Sweden”.

LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral premium driver.
Low ripple output current <4% to assure camera and scanner friendly performance.
Rotation 365°. Vertical adjustment 0-90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	1120g
Reflector	High efficiency metalized PC
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 34pcs/MCB 16A type B
Ripple out. current	< 4%. Flicker-free performance
Colour consistency	3 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Not dimmable



- White
- Black

MOCCA M PRO

Description	Reflector	CCT (K)	CRI	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																						
LIGHTSOURCE					LUMINAIRE			ART. No.																																																							
WARM WHITE 3000K (930)																																																															
MOCCA M Pro 3500lm SP 930	Spot 15°	3000K	92	3975	31W	3570	112	224310	224314																																																						
MOCCA M Pro 3500lm ME 930	Medium 25°	3000K	92	3975	31W	3570	112	224311	224315																																																						
MOCCA M Pro 3500lm FL 930	Flood 45°	3000K	92	3975	31W	3570	112	224312	224316																																																						
<table border="1"> <thead> <tr> <th colspan="3">Spot 15°</th> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 45°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,26</td> <td>23428</td> <td>1</td> <td>0,43</td> <td>11270</td> <td>1</td> <td>0,86</td> <td>5102</td> </tr> <tr> <td>2</td> <td>0,53</td> <td>5812</td> <td>2</td> <td>0,86</td> <td>2818</td> <td>2</td> <td>1,72</td> <td>1275</td> </tr> <tr> <td>3</td> <td>0,79</td> <td>2583</td> <td>3</td> <td>1,30</td> <td>1252</td> <td>3</td> <td>2,58</td> <td>567</td> </tr> <tr> <td>4</td> <td>1,06</td> <td>1453</td> <td>4</td> <td>1,72</td> <td>704</td> <td>4</td> <td>3,44</td> <td>319</td> </tr> </tbody> </table>					Spot 15°			Medium 25°			Flood 45°			m	∅	Lux	m	∅	Lux	m	∅	Lux	1	0,26	23428	1	0,43	11270	1	0,86	5102	2	0,53	5812	2	0,86	2818	2	1,72	1275	3	0,79	2583	3	1,30	1252	3	2,58	567	4	1,06	1453	4	1,72	704	4	3,44	319	<p>3000K 930 Spectral power distributions</p>				
Spot 15°			Medium 25°			Flood 45°																																																									
m	∅	Lux	m	∅	Lux	m	∅	Lux																																																							
1	0,26	23428	1	0,43	11270	1	0,86	5102																																																							
2	0,53	5812	2	0,86	2818	2	1,72	1275																																																							
3	0,79	2583	3	1,30	1252	3	2,58	567																																																							
4	1,06	1453	4	1,72	704	4	3,44	319																																																							
NEUTRAL WHITE 4000K (940)																																																															
MOCCA M Pro 3500lm SP 940	Spot 15°	4000K	92	4040	31W	3635	117	224350	224354																																																						
MOCCA M Pro 3500lm ME 940	Medium 25°	4000K	92	4070	31W	3635	117	224351	224355																																																						
MOCCA M Pro 3500lm FL 940	Flood 45°	4000K	92	4040	31W	3635	117	224352	224356																																																						
<table border="1"> <thead> <tr> <th colspan="3">Spot 15°</th> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 45°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,26</td> <td>23628</td> <td>1</td> <td>0,43</td> <td>11487</td> <td>1</td> <td>0,86</td> <td>5186</td> </tr> <tr> <td>2</td> <td>0,53</td> <td>5907</td> <td>2</td> <td>0,86</td> <td>2872</td> <td>2</td> <td>1,72</td> <td>1296</td> </tr> <tr> <td>3</td> <td>0,79</td> <td>3625</td> <td>3</td> <td>1,30</td> <td>1276</td> <td>3</td> <td>2,58</td> <td>576</td> </tr> <tr> <td>4</td> <td>1,06</td> <td>1495</td> <td>4</td> <td>1,72</td> <td>718</td> <td>4</td> <td>3,44</td> <td>324</td> </tr> </tbody> </table>					Spot 15°			Medium 25°			Flood 45°			m	∅	Lux	m	∅	Lux	m	∅	Lux	1	0,26	23628	1	0,43	11487	1	0,86	5186	2	0,53	5907	2	0,86	2872	2	1,72	1296	3	0,79	3625	3	1,30	1276	3	2,58	576	4	1,06	1495	4	1,72	718	4	3,44	324	<p>4000K 940 Spectral power distributions</p>				
Spot 15°			Medium 25°			Flood 45°																																																									
m	∅	Lux	m	∅	Lux	m	∅	Lux																																																							
1	0,26	23628	1	0,43	11487	1	0,86	5186																																																							
2	0,53	5907	2	0,86	2872	2	1,72	1296																																																							
3	0,79	3625	3	1,30	1276	3	2,58	576																																																							
4	1,06	1495	4	1,72	718	4	3,44	324																																																							

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.