


VINCI XS DIM

"Sidecar is our most compact version of spotlights. It is a traditional side-by-side solution, inspired by the sidecar version of a motorcycle. We created a design that places the point of rotation on the track as central as possible to avoid a big offset from the track, allowing a number of spotlights to visually work well together. Developed and produced in Sweden".

LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral driver.
Dimmable via phase-cut.
Rotation 365°. Vertical adjustment +/- 90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	700g
Reflector	High purity aluminium
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 50pcs/MCB 16A type B
Ripple out. current	< 20%
Colour consistency	3 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Phase-cut 100-20%



- White
- Black

VINCI XS DIM

Description	Reflector	CCT (K)	CRI	Lumen	Load	Lumen	Lm/W	Color																																		
								○ White	● Black																																	
LIGHTSOURCE					LUMINAIRE			ART. No.																																		
WARM WHITE 2700K (927)																																										
VINCI XS Dim 1000lm ME 927	Medium 25°	2700K	92	1055	10W	930	93	242121	242125																																	
VINCI XS Dim 1000lm FL 927	Flood 40°	2700K	92	1055	10W	930	93	242122	242126																																	
<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,44</td> <td>3660</td> <td>1</td> <td>0,70</td> <td>1995</td> </tr> <tr> <td>2</td> <td>0,88</td> <td>915</td> <td>2</td> <td>1,41</td> <td>499</td> </tr> <tr> <td>3</td> <td>1,32</td> <td>407</td> <td>3</td> <td>2,11</td> <td>222</td> </tr> <tr> <td>4</td> <td>1,76</td> <td>229</td> <td>4</td> <td>2,81</td> <td>125</td> </tr> </tbody> </table>		Medium 25°			Flood 40°			m	∅	Lux	m	∅	Lux	1	0,44	3660	1	0,70	1995	2	0,88	915	2	1,41	499	3	1,32	407	3	2,11	222	4	1,76	229	4	2,81	125	<p>2700K 827 Spectral power distributions</p>				
Medium 25°			Flood 40°																																							
m	∅	Lux	m	∅	Lux																																					
1	0,44	3660	1	0,70	1995																																					
2	0,88	915	2	1,41	499																																					
3	1,32	407	3	2,11	222																																					
4	1,76	229	4	2,81	125																																					
WARM WHITE 3000K (930)																																										
VINCI XS Dim 1000lm ME 930	Medium 25°	3000K	92	1220	10W	1070	107	242111	242115																																	
VINCI XS Dim 1000lm FL 930	Flood 40°	3000K	92	1220	10W	1070	107	242112	242116																																	
<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,44</td> <td>4210</td> <td>1</td> <td>0,70</td> <td>2295</td> </tr> <tr> <td>2</td> <td>0,88</td> <td>1053</td> <td>2</td> <td>1,41</td> <td>574</td> </tr> <tr> <td>3</td> <td>1,32</td> <td>468</td> <td>3</td> <td>2,11</td> <td>255</td> </tr> <tr> <td>4</td> <td>1,76</td> <td>263</td> <td>4</td> <td>2,81</td> <td>143</td> </tr> </tbody> </table>		Medium 25°			Flood 40°			m	∅	Lux	m	∅	Lux	1	0,44	4210	1	0,70	2295	2	0,88	1053	2	1,41	574	3	1,32	468	3	2,11	255	4	1,76	263	4	2,81	143	<p>3000K 930 Spectral power distributions</p>				
Medium 25°			Flood 40°																																							
m	∅	Lux	m	∅	Lux																																					
1	0,44	4210	1	0,70	2295																																					
2	0,88	1053	2	1,41	574																																					
3	1,32	468	3	2,11	255																																					
4	1,76	263	4	2,81	143																																					
NEUTRAL WHITE 4000K (940)																																										
VINCI XS Dim 1000lm ME 940	Medium 25°	4000K	92	1185	10W	1040	104	242151	242155																																	
VINCI XS Dim 1000lm FL 940	Flood 40°	4000K	92	1185	10W	1040	104	242152	242156																																	
<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,44</td> <td>4092</td> <td>1</td> <td>0,70</td> <td>2231</td> </tr> <tr> <td>2</td> <td>0,88</td> <td>1023</td> <td>2</td> <td>1,41</td> <td>558</td> </tr> <tr> <td>3</td> <td>1,32</td> <td>455</td> <td>3</td> <td>2,11</td> <td>248</td> </tr> <tr> <td>4</td> <td>1,76</td> <td>256</td> <td>4</td> <td>2,81</td> <td>139</td> </tr> </tbody> </table>		Medium 25°			Flood 40°			m	∅	Lux	m	∅	Lux	1	0,44	4092	1	0,70	2231	2	0,88	1023	2	1,41	558	3	1,32	455	3	2,11	248	4	1,76	256	4	2,81	139	<p>4000K 940 Spectral power distributions</p>				
Medium 25°			Flood 40°																																							
m	∅	Lux	m	∅	Lux																																					
1	0,44	4092	1	0,70	2231																																					
2	0,88	1023	2	1,41	558																																					
3	1,32	455	3	2,11	248																																					
4	1,76	256	4	2,81	139																																					

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.