


MOCCA S PRO

“Mocca - The all-in-one cylindrical solution. Mocca is our interpretation of an all integrated cylindrical spotlight. The cooling is passive, being all silent, by allowing cold air to flow from the middle of the cylinder and out in the back. By choosing Mocca you will get a uncluttered environment focusing on the essential: The simplicity of the spotlight and the effect of the light. Developed and produced in Sweden”.

LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral premium driver.
Low ripple output current <4% to assure camera and scanner friendly performance.
Rotation 365°. Vertical adjustment 0-90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	805g
Reflector	High purity aluminium
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 34pcs/MCB 16A type B
Ripple out. current	< 4%. Flicker-free performance
Colour consistency	3 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Not dimmable



- White
- Black

MOCCA S PRO

Description	Reflector	CCT (K)	CRI	Load	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																																																																																																		
LIGHTSOURCE						LUMINAIRE			ART. No.																																																																																																																																			
WARM WHITE 3000K (930)																																																																																																																																												
MOCCA S Pro 1500lm SP 930	Spot 15°	3000K	92	11W	1640	13W	1420	108	222110	222114																																																																																																																																		
MOCCA S Pro 1500lm ME 930	Medium 25°	3000K	92	11W	1640	13W	1420	108	222111	222115																																																																																																																																		
MOCCA S Pro 1500lm FL 930	Flood 40°	3000K	92	11W	1640	13W	1420	108	222112	222116																																																																																																																																		
MOCCA S Pro 2500lm SP 930	Spot 15°	3000K	92	20W	2705	23W	2380	102	222210	222214																																																																																																																																		
MOCCA S Pro 2500lm ME 930	Medium 25°	3000K	92	20W	2705	23W	2380	102	222211	222215																																																																																																																																		
MOCCA S Pro 2500lm FL 930	Flood 40°	3000K	92	20W	2705	23W	2380	102	222212	222216																																																																																																																																		
<table border="1"> <thead> <tr> <th colspan="4">Spot</th> <th colspan="4">Medium</th> <th colspan="4">Flood</th> </tr> <tr> <th colspan="2"></th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> <th colspan="2"></th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> <th colspan="2"></th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>7078</td> <td>11793</td> <td>1</td> <td>0,41</td> <td>4653</td> <td>7798</td> <td>1</td> <td>0,74</td> <td>2589</td> <td>4316</td> <td>1</td> <td>0,28</td> <td>7078</td> <td>11793</td> <td>1</td> <td>0,41</td> <td>4653</td> <td>7798</td> </tr> <tr> <td>2</td> <td>0,57</td> <td>1769</td> <td>2948</td> <td>2</td> <td>0,83</td> <td>1163</td> <td>1949</td> <td>2</td> <td>1,42</td> <td>647</td> <td>1079</td> <td>2</td> <td>0,57</td> <td>1769</td> <td>2948</td> <td>2</td> <td>0,83</td> <td>1163</td> <td>1949</td> </tr> <tr> <td>3</td> <td>0,85</td> <td>786</td> <td>1310</td> <td>3</td> <td>1,23</td> <td>517</td> <td>866</td> <td>3</td> <td>2,18</td> <td>288</td> <td>480</td> <td>3</td> <td>0,85</td> <td>786</td> <td>1310</td> <td>3</td> <td>1,23</td> <td>517</td> <td>866</td> </tr> <tr> <td>4</td> <td>1,13</td> <td>442</td> <td>737</td> <td>4</td> <td>1,65</td> <td>291</td> <td>487</td> <td>4</td> <td>2,91</td> <td>162</td> <td>270</td> <td>4</td> <td>1,13</td> <td>442</td> <td>737</td> <td>4</td> <td>1,65</td> <td>291</td> <td>487</td> </tr> </tbody> </table>											Spot				Medium				Flood						1500lm		2500lm				1500lm		2500lm				1500lm		2500lm		m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	7078	11793	1	0,41	4653	7798	1	0,74	2589	4316	1	0,28	7078	11793	1	0,41	4653	7798	2	0,57	1769	2948	2	0,83	1163	1949	2	1,42	647	1079	2	0,57	1769	2948	2	0,83	1163	1949	3	0,85	786	1310	3	1,23	517	866	3	2,18	288	480	3	0,85	786	1310	3	1,23	517	866	4	1,13	442	737	4	1,65	291	487	4	2,91	162	270	4	1,13	442	737	4	1,65	291	487
Spot				Medium				Flood																																																																																																																																				
		1500lm		2500lm				1500lm		2500lm				1500lm		2500lm																																																																																																																												
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																									
1	0,28	7078	11793	1	0,41	4653	7798	1	0,74	2589	4316	1	0,28	7078	11793	1	0,41	4653	7798																																																																																																																									
2	0,57	1769	2948	2	0,83	1163	1949	2	1,42	647	1079	2	0,57	1769	2948	2	0,83	1163	1949																																																																																																																									
3	0,85	786	1310	3	1,23	517	866	3	2,18	288	480	3	0,85	786	1310	3	1,23	517	866																																																																																																																									
4	1,13	442	737	4	1,65	291	487	4	2,91	162	270	4	1,13	442	737	4	1,65	291	487																																																																																																																									
<p>3000K 930 Spectral power distributions</p>																																																																																																																																												
NEUTRAL WHITE 4000K (940)																																																																																																																																												
MOCCA S Pro 1500lm SP 940	Spot 15°	4000K	92	11W	1770	13W	1530	116	222150	222154																																																																																																																																		
MOCCA S Pro 1500lm ME 940	Medium 25°	4000K	92	11W	1770	13W	1530	116	222151	222155																																																																																																																																		
MOCCA S Pro 1500lm FL 940	Flood 40°	4000K	92	11W	1770	13W	1530	116	222152	222156																																																																																																																																		
MOCCA S Pro 2500lm SP 940	Spot 15°	4000K	92	20W	2920	23W	2570	111	222250	222254																																																																																																																																		
MOCCA S Pro 2500lm ME 940	Medium 25°	4000K	92	20W	2920	23W	2570	111	222251	222255																																																																																																																																		
MOCCA S Pro 2500lm FL 940	Flood 40°	4000K	92	20W	2920	23W	2570	111	222252	222256																																																																																																																																		
<table border="1"> <thead> <tr> <th colspan="4">Spot</th> <th colspan="4">Medium</th> <th colspan="4">Flood</th> </tr> <tr> <th colspan="2"></th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> <th colspan="2"></th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> <th colspan="2"></th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>7566</td> <td>12810</td> <td>1</td> <td>0,41</td> <td>5016</td> <td>8410</td> <td>1</td> <td>0,74</td> <td>2774</td> <td>4653</td> <td>1</td> <td>0,28</td> <td>7566</td> <td>12810</td> <td>1</td> <td>0,41</td> <td>5016</td> <td>8410</td> </tr> <tr> <td>2</td> <td>0,57</td> <td>1892</td> <td>3202</td> <td>2</td> <td>0,83</td> <td>1254</td> <td>2102</td> <td>2</td> <td>1,42</td> <td>694</td> <td>1163</td> <td>2</td> <td>0,57</td> <td>1892</td> <td>3202</td> <td>2</td> <td>0,83</td> <td>1254</td> <td>2102</td> </tr> <tr> <td>3</td> <td>0,85</td> <td>841</td> <td>1423</td> <td>3</td> <td>1,23</td> <td>557</td> <td>934</td> <td>3</td> <td>2,18</td> <td>308</td> <td>517</td> <td>3</td> <td>0,85</td> <td>841</td> <td>1423</td> <td>3</td> <td>1,23</td> <td>557</td> <td>934</td> </tr> <tr> <td>4</td> <td>1,13</td> <td>473</td> <td>801</td> <td>4</td> <td>1,65</td> <td>313</td> <td>526</td> <td>4</td> <td>2,91</td> <td>173</td> <td>291</td> <td>4</td> <td>1,13</td> <td>473</td> <td>801</td> <td>4</td> <td>1,65</td> <td>313</td> <td>526</td> </tr> </tbody> </table>											Spot				Medium				Flood						1500lm		2500lm				1500lm		2500lm				1500lm		2500lm		m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	7566	12810	1	0,41	5016	8410	1	0,74	2774	4653	1	0,28	7566	12810	1	0,41	5016	8410	2	0,57	1892	3202	2	0,83	1254	2102	2	1,42	694	1163	2	0,57	1892	3202	2	0,83	1254	2102	3	0,85	841	1423	3	1,23	557	934	3	2,18	308	517	3	0,85	841	1423	3	1,23	557	934	4	1,13	473	801	4	1,65	313	526	4	2,91	173	291	4	1,13	473	801	4	1,65	313	526
Spot				Medium				Flood																																																																																																																																				
		1500lm		2500lm				1500lm		2500lm				1500lm		2500lm																																																																																																																												
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																									
1	0,28	7566	12810	1	0,41	5016	8410	1	0,74	2774	4653	1	0,28	7566	12810	1	0,41	5016	8410																																																																																																																									
2	0,57	1892	3202	2	0,83	1254	2102	2	1,42	694	1163	2	0,57	1892	3202	2	0,83	1254	2102																																																																																																																									
3	0,85	841	1423	3	1,23	557	934	3	2,18	308	517	3	0,85	841	1423	3	1,23	557	934																																																																																																																									
4	1,13	473	801	4	1,65	313	526	4	2,91	173	291	4	1,13	473	801	4	1,65	313	526																																																																																																																									
<p>4000K 940 Spectral power distributions</p>																																																																																																																																												

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.