


MOCCA S PRO

“Mocca - The all-in-one cylindrical solution. Mocca is our interpretation of an all integrated cylindrical spotlight. The cooling is passive, being all silent, by allowing cold air to flow from the middle of the cylinder and out in the back. By choosing Mocca you will get a uncluttered environment focusing on the essential: The simplicity of the spotlight and the effect of the light. Developed and produced in Sweden”.

LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral premium driver.
Low ripple output current <4% to assure camera and scanner friendly performance.
Rotation 365°. Vertical adjustment 0-90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	805g
Reflector	High purity aluminium
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 34pcs/MCB 16A type B
Ripple out. current	< 4%. Flicker-free performance
Colour consistency	3 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Not dimmable



- White
- Black

MOCCA S PRO

Description	Reflector	CCT (K)	CRI	Load	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																																																																																																															
LIGHTSOURCE						LUMINAIRE			ART. No.																																																																																																																																																
WARM WHITE 3000K (830)																																																																																																																																																									
MOCCA S Pro 1500lm SP 830	Spot 15°	3000K	82	11W	1655	13W	1480	114	222100	222104																																																																																																																																															
MOCCA S Pro 1500lm ME 830	Medium 25°	3000K	82	11W	1655	13W	1480	114	222101	222105																																																																																																																																															
MOCCA S Pro 1500lm FL 830	Flood 40°	3000K	82	11W	1655	13W	1480	114	222102	222106																																																																																																																																															
MOCCA S Pro 2500lm SP 830	Spot 15°	3000K	82	20W	2820	23W	2540	110	222200	222204																																																																																																																																															
MOCCA S Pro 2500lm ME 830	Medium 25°	3000K	82	20W	2820	23W	2540	110	222201	222205																																																																																																																																															
MOCCA S Pro 2500lm FL 830	Flood 40°	3000K	82	20W	2820	23W	2540	110	222202	222206																																																																																																																																															
<table border="1"> <thead> <tr> <th colspan="2">Spot</th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>7606</td> <td>13162</td> <td>1</td> <td>0,42</td> <td>4763</td> <td>8275</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>1902</td> <td>3291</td> <td>2</td> <td>0,84</td> <td>1191</td> <td>2069</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>845</td> <td>1462</td> <td>3</td> <td>1,25</td> <td>529</td> <td>919</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>475</td> <td>823</td> <td>4</td> <td>1,70</td> <td>298</td> <td>517</td> </tr> </tbody> </table>						Spot		1500lm		2500lm		m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	7606	13162	1	0,42	4763	8275	2	0,56	1902	3291	2	0,84	1191	2069	3	0,84	845	1462	3	1,25	529	919	4	1,12	475	823	4	1,70	298	517	<table border="1"> <thead> <tr> <th colspan="2">Medium</th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,42</td> <td>4763</td> <td>8275</td> <td>1</td> <td>0,74</td> <td>2646</td> <td>4518</td> </tr> <tr> <td>2</td> <td>0,84</td> <td>1191</td> <td>2069</td> <td>2</td> <td>1,42</td> <td>662</td> <td>1130</td> </tr> <tr> <td>3</td> <td>1,25</td> <td>529</td> <td>919</td> <td>3</td> <td>2,18</td> <td>294</td> <td>502</td> </tr> <tr> <td>4</td> <td>1,70</td> <td>298</td> <td>517</td> <td>4</td> <td>2,91</td> <td>165</td> <td>282</td> </tr> </tbody> </table>						Medium		1500lm		2500lm		m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,42	4763	8275	1	0,74	2646	4518	2	0,84	1191	2069	2	1,42	662	1130	3	1,25	529	919	3	2,18	294	502	4	1,70	298	517	4	2,91	165	282	<table border="1"> <thead> <tr> <th colspan="2">Flood</th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,74</td> <td>2646</td> <td>4518</td> <td>1</td> <td>1,42</td> <td>662</td> <td>1130</td> </tr> <tr> <td>2</td> <td>1,42</td> <td>662</td> <td>1130</td> <td>2</td> <td>2,18</td> <td>294</td> <td>502</td> </tr> <tr> <td>3</td> <td>2,18</td> <td>294</td> <td>502</td> <td>3</td> <td>2,91</td> <td>165</td> <td>282</td> </tr> </tbody> </table>						Flood		1500lm		2500lm		m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,74	2646	4518	1	1,42	662	1130	2	1,42	662	1130	2	2,18	294	502	3	2,18	294	502	3	2,91	165	282	3000K 830 Spectral power distributions 					
Spot		1500lm		2500lm																																																																																																																																																					
m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																																		
1	0,28	7606	13162	1	0,42	4763	8275																																																																																																																																																		
2	0,56	1902	3291	2	0,84	1191	2069																																																																																																																																																		
3	0,84	845	1462	3	1,25	529	919																																																																																																																																																		
4	1,12	475	823	4	1,70	298	517																																																																																																																																																		
Medium		1500lm		2500lm																																																																																																																																																					
m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																																		
1	0,42	4763	8275	1	0,74	2646	4518																																																																																																																																																		
2	0,84	1191	2069	2	1,42	662	1130																																																																																																																																																		
3	1,25	529	919	3	2,18	294	502																																																																																																																																																		
4	1,70	298	517	4	2,91	165	282																																																																																																																																																		
Flood		1500lm		2500lm																																																																																																																																																					
m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																																		
1	0,74	2646	4518	1	1,42	662	1130																																																																																																																																																		
2	1,42	662	1130	2	2,18	294	502																																																																																																																																																		
3	2,18	294	502	3	2,91	165	282																																																																																																																																																		
WARM WHITE 3000K (930)																																																																																																																																																									
MOCCA S Pro 1500lm SP 930	Spot 15°	3000K	92	11W	1430	13W	1290	99	222110	222114																																																																																																																																															
MOCCA S Pro 1500lm ME 930	Medium 25°	3000K	92	11W	1460	13W	1290	99	222111	222115																																																																																																																																															
MOCCA S Pro 1500lm FL 930	Flood 40°	3000K	92	11W	1460	13W	1290	99	222112	222116																																																																																																																																															
MOCCA S Pro 2500lm SP 930	Spot 15°	3000K	92	20W	2455	23W	2210	96	222210	222214																																																																																																																																															
MOCCA S Pro 2500lm ME 930	Medium 25°	3000K	92	20W	2455	23W	2210	96	222211	222215																																																																																																																																															
MOCCA S Pro 2500lm FL 930	Flood 40°	3000K	92	20W	2455	23W	2210	96	222212	222216																																																																																																																																															
<table border="1"> <thead> <tr> <th colspan="2">Spot</th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>6643</td> <td>11617</td> <td>1</td> <td>0,42</td> <td>4208</td> <td>7290</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>1661</td> <td>2904</td> <td>2</td> <td>0,84</td> <td>1052</td> <td>1823</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>738</td> <td>1291</td> <td>3</td> <td>1,25</td> <td>468</td> <td>810</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>415</td> <td>726</td> <td>4</td> <td>1,70</td> <td>263</td> <td>456</td> </tr> </tbody> </table>						Spot		1500lm		2500lm		m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	6643	11617	1	0,42	4208	7290	2	0,56	1661	2904	2	0,84	1052	1823	3	0,84	738	1291	3	1,25	468	810	4	1,12	415	726	4	1,70	263	456	<table border="1"> <thead> <tr> <th colspan="2">Medium</th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,42</td> <td>4208</td> <td>7290</td> <td>1</td> <td>0,74</td> <td>2297</td> <td>3983</td> </tr> <tr> <td>2</td> <td>0,84</td> <td>1052</td> <td>1823</td> <td>2</td> <td>1,42</td> <td>574</td> <td>996</td> </tr> <tr> <td>3</td> <td>1,25</td> <td>468</td> <td>810</td> <td>3</td> <td>2,18</td> <td>255</td> <td>443</td> </tr> <tr> <td>4</td> <td>1,70</td> <td>263</td> <td>456</td> <td>4</td> <td>2,91</td> <td>144</td> <td>249</td> </tr> </tbody> </table>						Medium		1500lm		2500lm		m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,42	4208	7290	1	0,74	2297	3983	2	0,84	1052	1823	2	1,42	574	996	3	1,25	468	810	3	2,18	255	443	4	1,70	263	456	4	2,91	144	249	<table border="1"> <thead> <tr> <th colspan="2">Flood</th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,74</td> <td>2297</td> <td>3983</td> <td>1</td> <td>1,42</td> <td>574</td> <td>996</td> </tr> <tr> <td>2</td> <td>1,42</td> <td>574</td> <td>996</td> <td>2</td> <td>2,18</td> <td>255</td> <td>443</td> </tr> <tr> <td>3</td> <td>2,18</td> <td>255</td> <td>443</td> <td>3</td> <td>2,91</td> <td>144</td> <td>249</td> </tr> </tbody> </table>						Flood		1500lm		2500lm		m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,74	2297	3983	1	1,42	574	996	2	1,42	574	996	2	2,18	255	443	3	2,18	255	443	3	2,91	144	249	3000K 930 Spectral power distributions 					
Spot		1500lm		2500lm																																																																																																																																																					
m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																																		
1	0,28	6643	11617	1	0,42	4208	7290																																																																																																																																																		
2	0,56	1661	2904	2	0,84	1052	1823																																																																																																																																																		
3	0,84	738	1291	3	1,25	468	810																																																																																																																																																		
4	1,12	415	726	4	1,70	263	456																																																																																																																																																		
Medium		1500lm		2500lm																																																																																																																																																					
m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																																		
1	0,42	4208	7290	1	0,74	2297	3983																																																																																																																																																		
2	0,84	1052	1823	2	1,42	574	996																																																																																																																																																		
3	1,25	468	810	3	2,18	255	443																																																																																																																																																		
4	1,70	263	456	4	2,91	144	249																																																																																																																																																		
Flood		1500lm		2500lm																																																																																																																																																					
m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																																		
1	0,74	2297	3983	1	1,42	574	996																																																																																																																																																		
2	1,42	574	996	2	2,18	255	443																																																																																																																																																		
3	2,18	255	443	3	2,91	144	249																																																																																																																																																		
NEUTRAL WHITE 4000K (840)																																																																																																																																																									
MOCCA S Pro 1500lm SP 840	Spot 15°	4000K	82	11W	1730	13W	1545	119	222140	222144																																																																																																																																															
MOCCA S Pro 1500lm ME 840	Medium 25°	4000K	82	11W	1730	13W	1545	119	222141	222145																																																																																																																																															
MOCCA S Pro 1500lm FL 840	Flood 40°	4000K	82	11W	1730	13W	1545	119	222142	222146																																																																																																																																															
MOCCA S Pro 2500lm SP 840	Spot 15°	4000K	82	20W	2960	23W	2660	115	222240	222244																																																																																																																																															
MOCCA S Pro 2500lm ME 840	Medium 25°	4000K	82	20W	2960	23W	2660	115	222241	222245																																																																																																																																															
MOCCA S Pro 2500lm FL 840	Flood 40°	4000K	82	20W	2960	23W	2660	115	222242	222246																																																																																																																																															
<table border="1"> <thead> <tr> <th colspan="2">Spot</th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>8043</td> <td>13682</td> <td>1</td> <td>0,42</td> <td>5058</td> <td>8702</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>2011</td> <td>3421</td> <td>2</td> <td>0,84</td> <td>1265</td> <td>2176</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>894</td> <td>1520</td> <td>3</td> <td>1,25</td> <td>562</td> <td>967</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>503</td> <td>855</td> <td>4</td> <td>1,70</td> <td>316</td> <td>544</td> </tr> </tbody> </table>						Spot		1500lm		2500lm		m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	8043	13682	1	0,42	5058	8702	2	0,56	2011	3421	2	0,84	1265	2176	3	0,84	894	1520	3	1,25	562	967	4	1,12	503	855	4	1,70	316	544	<table border="1"> <thead> <tr> <th colspan="2">Medium</th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,42</td> <td>5058</td> <td>8702</td> <td>1</td> <td>0,74</td> <td>2733</td> <td>4746</td> </tr> <tr> <td>2</td> <td>0,84</td> <td>1265</td> <td>2176</td> <td>2</td> <td>1,42</td> <td>683</td> <td>1187</td> </tr> <tr> <td>3</td> <td>1,25</td> <td>562</td> <td>967</td> <td>3</td> <td>2,18</td> <td>304</td> <td>527</td> </tr> <tr> <td>4</td> <td>1,70</td> <td>316</td> <td>544</td> <td>4</td> <td>2,91</td> <td>171</td> <td>297</td> </tr> </tbody> </table>						Medium		1500lm		2500lm		m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,42	5058	8702	1	0,74	2733	4746	2	0,84	1265	2176	2	1,42	683	1187	3	1,25	562	967	3	2,18	304	527	4	1,70	316	544	4	2,91	171	297	<table border="1"> <thead> <tr> <th colspan="2">Flood</th> <th colspan="2">1500lm</th> <th colspan="2">2500lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,74</td> <td>2733</td> <td>4746</td> <td>1</td> <td>1,42</td> <td>683</td> <td>1187</td> </tr> <tr> <td>2</td> <td>1,42</td> <td>683</td> <td>1187</td> <td>2</td> <td>2,18</td> <td>304</td> <td>527</td> </tr> <tr> <td>3</td> <td>2,18</td> <td>304</td> <td>527</td> <td>3</td> <td>2,91</td> <td>171</td> <td>297</td> </tr> </tbody> </table>						Flood		1500lm		2500lm		m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,74	2733	4746	1	1,42	683	1187	2	1,42	683	1187	2	2,18	304	527	3	2,18	304	527	3	2,91	171	297	4000K 840 Spectral power distributions 					
Spot		1500lm		2500lm																																																																																																																																																					
m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																																		
1	0,28	8043	13682	1	0,42	5058	8702																																																																																																																																																		
2	0,56	2011	3421	2	0,84	1265	2176																																																																																																																																																		
3	0,84	894	1520	3	1,25	562	967																																																																																																																																																		
4	1,12	503	855	4	1,70	316	544																																																																																																																																																		
Medium		1500lm		2500lm																																																																																																																																																					
m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																																		
1	0,42	5058	8702	1	0,74	2733	4746																																																																																																																																																		
2	0,84	1265	2176	2	1,42	683	1187																																																																																																																																																		
3	1,25	562	967	3	2,18	304	527																																																																																																																																																		
4	1,70	316	544	4	2,91	171	297																																																																																																																																																		
Flood		1500lm		2500lm																																																																																																																																																					
m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																																																																		
1	0,74	2733	4746	1	1,42	683	1187																																																																																																																																																		
2	1,42	683	1187	2	2,18	304	527																																																																																																																																																		
3	2,18	304	527	3	2,91	171	297																																																																																																																																																		

MOCCA S PRO

Description	Reflector	CCT (K)	CRI	Load	Lumen	Load	Lumen	Lm/W	○ White	● Black
LIGHTSOURCE						LUMINAIRE			ART. No.	
NEUTRAL WHITE 4000K (940)										
MOCCA S Pro 1500lm SP 940	Spot 15°	4000K	92	11W	1570	13W	1395	107	222150	222154
MOCCA S Pro 1500lm ME 940	Medium 25°	4000K	92	11W	1570	13W	1395	107	222151	222155
MOCCA S Pro 1500lm FL 940	Flood 40°	4000K	92	11W	1570	13W	1395	107	222152	222156
MOCCA S Pro 2500lm SP 940	Spot 15°	4000K	92	20W	2570	23W	2290	100	222250	222254
MOCCA S Pro 2500lm ME 940	Medium 25°	4000K	92	20W	2570	23W	2290	100	222251	222255
MOCCA S Pro 2500lm FL 940	Flood 40°	4000K	92	20W	2570	23W	2290	100	222252	222256

Spot				Medium				Flood			
		1500lm	2500lm			1500lm	2500lm			1500lm	2500lm
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux
1	0,28	6938	11354	1	0,42	4555	7505	1	0,74	2535	4147
2	0,56	1735	2839	2	0,84	1139	1876	2	1,42	634	1037
3	0,84	771	1262	3	1,25	506	834	3	2,18	282	461
4	1,12	434	710	4	1,70	285	469	4	2,91	158	259

4000K 940 Spectral power distributions

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.