


VINCI XS DIM

"Sidecar is our most compact version of spotlights. It is a traditional side-by-side solution, inspired by the sidecar version of a motorcycle. We created a design that places the point of rotation on the track as central as possible to avoid a big offset from the track, allowing a number of spotlights to visually work well together. Developed and produced in Sweden".

LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral driver.
Dimmable via phase-cut.
Rotation 365°. Vertical adjustment +/- 90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	700g
Reflector	High purity aluminium
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 50pcs/MCB 16A type B
Ripple out. current	< 20%
Colour consistency	3 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Phase-cut 100-20%



- White
- Black

VINCI XS DIM

Description	Reflector	CCT (K)	CRI	Load	Lumen	Load	Lumen	Lm/W	○ White	● Black																																	
						LIGHTSOURCE			LUMINAIRE			ART. No.																															
WARM WHITE 2700K (927)																																											
VINCI XS Dim 1000lm ME 927	Medium 25°	2700K	92	8W	1090	10W	990	99	242121	242125																																	
VINCI XS Dim 1000lm FL 927 Flood 40°		2700K	92	8W	1090	10W	990	99	242122	242126																																	
	<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,44</td> <td>3900</td> </tr> <tr> <td>2</td> <td>0,88</td> <td>975</td> </tr> <tr> <td>3</td> <td>1,32</td> <td>433</td> </tr> <tr> <td>4</td> <td>1,76</td> <td>244</td> </tr> </tbody> </table>	Medium 25°			m	∅	Lux	1	0,44	3900	2	0,88	975	3	1,32	433	4	1,76	244	<table border="1"> <thead> <tr> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,70</td> <td>2117</td> </tr> <tr> <td>2</td> <td>1,41</td> <td>529</td> </tr> <tr> <td>3</td> <td>2,11</td> <td>235</td> </tr> <tr> <td>4</td> <td>2,81</td> <td>132</td> </tr> </tbody> </table>	Flood 40°			m	∅	Lux	1	0,70	2117	2	1,41	529	3	2,11	235	4	2,81	132	<p>2700K 827 Spectral power distributions</p>				
Medium 25°																																											
m	∅	Lux																																									
1	0,44	3900																																									
2	0,88	975																																									
3	1,32	433																																									
4	1,76	244																																									
Flood 40°																																											
m	∅	Lux																																									
1	0,70	2117																																									
2	1,41	529																																									
3	2,11	235																																									
4	2,81	132																																									
WARM WHITE 3000K (930)																																											
VINCI XS Dim 1000lm ME 930	Medium 25°	3000K	92	8W	1160	10W	1040	104	242111	242115																																	
VINCI XS Dim 1000lm FL 930 Flood 40°		3000K	92	8W	1160	10W	1040	104	242112	242116																																	
	<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,44</td> <td>4109</td> </tr> <tr> <td>2</td> <td>0,88</td> <td>1027</td> </tr> <tr> <td>3</td> <td>1,32</td> <td>457</td> </tr> <tr> <td>4</td> <td>1,76</td> <td>257</td> </tr> </tbody> </table>	Medium 25°			m	∅	Lux	1	0,44	4109	2	0,88	1027	3	1,32	457	4	1,76	257	<table border="1"> <thead> <tr> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,70</td> <td>2227</td> </tr> <tr> <td>2</td> <td>1,41</td> <td>557</td> </tr> <tr> <td>3</td> <td>2,11</td> <td>247</td> </tr> <tr> <td>4</td> <td>2,81</td> <td>139</td> </tr> </tbody> </table>	Flood 40°			m	∅	Lux	1	0,70	2227	2	1,41	557	3	2,11	247	4	2,81	139	<p>3000K 930 Spectral power distributions</p>				
Medium 25°																																											
m	∅	Lux																																									
1	0,44	4109																																									
2	0,88	1027																																									
3	1,32	457																																									
4	1,76	257																																									
Flood 40°																																											
m	∅	Lux																																									
1	0,70	2227																																									
2	1,41	557																																									
3	2,11	247																																									
4	2,81	139																																									
NEUTRAL WHITE 4000K (940)																																											
VINCI XS Dim 1000lm ME 940	Medium 25°	4000K	92	8W	1230	10W	1110	111	242151	242155																																	
VINCI XS Dim 1000lm FL 940 Flood 40°		4000K	92	8W	1230	10W	1110	111	242152	242156																																	
	<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,44</td> <td>4380</td> </tr> <tr> <td>2</td> <td>0,88</td> <td>1095</td> </tr> <tr> <td>3</td> <td>1,32</td> <td>487</td> </tr> <tr> <td>4</td> <td>1,76</td> <td>274</td> </tr> </tbody> </table>	Medium 25°			m	∅	Lux	1	0,44	4380	2	0,88	1095	3	1,32	487	4	1,76	274	<table border="1"> <thead> <tr> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,70</td> <td>2381</td> </tr> <tr> <td>2</td> <td>1,41</td> <td>595</td> </tr> <tr> <td>3</td> <td>2,11</td> <td>265</td> </tr> <tr> <td>4</td> <td>2,81</td> <td>149</td> </tr> </tbody> </table>	Flood 40°			m	∅	Lux	1	0,70	2381	2	1,41	595	3	2,11	265	4	2,81	149	<p>4000K 940 Spectral power distributions</p>				
Medium 25°																																											
m	∅	Lux																																									
1	0,44	4380																																									
2	0,88	1095																																									
3	1,32	487																																									
4	1,76	274																																									
Flood 40°																																											
m	∅	Lux																																									
1	0,70	2381																																									
2	1,41	595																																									
3	2,11	265																																									
4	2,81	149																																									

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/- 150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.